
Part 1: Charging instructions

- 1.Connect the Micro-USB line to the charging case to let the charging case fully charged. 2. When you need to charge the hearing aid.put
- the machines into the charging case. 3. During charge period the indication light will
- 4. Once charging is complete the indication

show BLUE.



Part 2: Operation Instructions

- 1.Before use, make sure the amplifier is fully charged.
- 2. Taking out the amplifier from the charging case.
- 3. Press up to 3 seconds to turn on when you hear twice "beep".

4. While covering the microphone with your fingertip to advoid the





high-pitched sound, place the amplifier into ear. 5. Make sure you achieve a comfortable fit, and that the microphone is not being blocked.

6.To turn off the amplifier.press up to 3 seconds when you hear twice "beep".

Volume control:

Press the volume button to adjust the volume. There are 6 sound levels of volume, and you will hear a "beep" sound each time a level goes up. You will hear three times "beep" at the max volume. If you press again, it will go back to the lowest volume.

Part 3: Specification

Maximum OSPL90:	≤120dB+3dB
High frequency	
average OSPL90:	103dB±4dB
Average gain:	23dB±5dB
Equivalent input	
noise level: ≤35dB	
Total harmonic distortion:	≤10%
Frequency response	
range:	300Hz∼3500Hz
Rated power supply	
current consumption:	≤6mA
Work time:	12-15hours
Charging time:	90min-2hours

Part 3: Specification

Charging case	
working current:	≤70mA
Charging case	
working voltage:	3.7V
Charging case	
charging time:	90min
Hearing aid charging	
current:	≤30mA
Hearing aid charging	
voltage:	4.2V
Hearing aid charging	
times (double machine):	3-4times

Instruction manual Model: JH-A39

